










INDUSTRIAL RANGE

GENSET 500 KVA IVECO / LEROY SOMER

1. MAIN FEATURES

T Three-phase	 Diesel	
 Iveco / C16 TE1W	 Leroy Somer / TAL0473C	
 Grupel / G545	Hz 50 Hz	
 1500 r.p.m.	V 400 V	
cos φ 0.8	 800 A	
Standby Power(ESP)	550 kVA	440 kW
Prime Power (PRP)	500 kVA	400 kW
Continuous Power(COP)	-	-

SOUNDPROOF

Length (L)	4020 mm	
Height (H)	2155 mm	
Width (W)	1430 mm	
Weight	3828.9 kg	
Fuel tank daily capacity	1000 L	
Acoustic pressure level @ 1m		87 ± 2 dB(A)
Acoustic pressure level @ 7m		79 ± 2 dB(A)

2. ROOM INSTALLATION

EXHAUST SYSTEM	50 Hz		
	COP	PRP	ESP
Exhaust gas temperature (°C)	-	557	-
Exhaust gas flow (m³/min)	-	-	2548
Evacuated heat (kW)	-	375.3	416.3
Maximum back pressure (kPa)		7	
Exhaust silencer attenuation (dB)		18-25	
Output diameter (mm)		168	

VENTILATION SYSTEMS	50 Hz		
	COP	PRP	ESP
Combustion air flow (m³/min)	-	43.8	-
Cooling airflow (m³/min)		631.8	
Maximum load losses (Pa)		196	
Alternator cooling air flow (m³/min)		54	

RADIATION	50 Hz		
	COP	PRP	ESP
Engine (kW)	-	-	-
Alternator (kW)	22.4	22.4	25.52



3. ENGINE SPECIFICATIONS

GENERAL SPECIFICATIONS		50Hz
Model		C16 TE1W
Emissions (UE/USEPA)		Not applicable / Not applicable
Performance grade		G2
Operating method		4 stroke
Fuel type		Diesel
Refrigeration system		Closed water circuit / antifreeze
Aspiration system		Turbo-intercooled
Injection system		Common-rail
No. and Cylinder arrangement		6 In-line
Displacement (L)		15.9
Cylinder bore (mm)		141
Cylinder stroke (mm)		170
Compression ratio		16,5:1
Regulation		Electronic
Rotation speed (r.p.m.)		1500
Piston speed (m/s)		8.5
Gross power COP (kWm)		-
Gross power PRP (kWm)		516.8
Gross power ESP (kWm)		570
Fan Power (kWm)		- / 10 / 11
Net Power COP (kWm)		-
Net Power PRP (kWm)		505.8
Net Power ESP (kWm)		559
BMEP COP (kPa)		-
BMEP PRP (kPa)		2560
BMEP ESP (kPa)		2860



CONSUMPTION			50 Hz
Fuel consumption	l/h		g/kWh
ESP	130.1		194
PRP	116.4		191
COP	-		-
75%	87.3		191
50%	59.1		194
Oil consumption	< 0.2% of fuel consumption		

REFERENCE CONDITIONS	
Temperature (°C)	25
Atmospheric pressure (kPa)	100

CAPACITY (°C)	
Coolant (L)	25.5
Oil (L)	38

STARTING SYSTEM	
Voltage (V)	24
Power (kW)	5.5
Battery (Ah)	140

4. ALTERNATOR SPECIFICATIONS

GENERAL SPECIFICATIONS	
Model	TAL0473C
Phases No.	Three-phase
Protection	IP23
Insulation	H
Temperature rise	H
R.F.I. telephone interference	THF < 2%
R.F.I. Suppression	IEC 61000-6-2/3/4, VDE 0875G/N, EN 55011
Coupling	Flexible disks
Support	Single bearing



Wave form distortion with no load	< 1,5%
Wave form distortion with balanced linear load	< 5%
Winding Leads	6
Excitation (standard/optional)	SHUNT / AREP+ / PMG
AVR Model (standard/optional)	R150 / R180 / R180
Voltage Regulation (standard/optional)	± 0,8 % / ± 0,5 % / ± 0,5 %
Icc (standard/optional)	- / 2,7In:5s

PF (cos Ø)	Phase	Voltage (V)	Power PRP/ESP (kVA)	Efficiency PRP/ESP (%)	Xd	X'd	X''d
0.8	Three-phase	400	500 / 550	94.4 / 94.2	3.32	0.167	0.117



5. CONTROL PANEL



GENSET	Grupel G545
Voltage (F-F / F-N)	● / ●
Current intensity	●
Frequency	●
RMS Values	●
Generator phase sequence	●
Generator earth current [a]	○
No. of registered events	400
Real time clock	●
PIN Protection	●
kWh, kVAR, kVAh, kVARh, cos Ø	●
Synchroscope [i]	○
No. of available outputs [b]	4
Indication of alarms on LCD	●
Hours of engine operation	●
Total no. of LED indicators	15
No. of LED alarms	4
Sound signalling alarms	-
Schedule	●
Fuel level	●

ELECTRICAL GRID	Grupel G545
Voltage (F-F / F-N)	● / ●
Current [a]	○
Frequency	●
kVA,kW, cos Ø [a]	○
Inversion control between main-group	●

PROTECTIONS AND ALARMS	Grupel G545
High / low battery voltage	A
Failure in battery charge alternator	A
Failure to stop	A/S
Failure to start	A/S
Low fuel level	A/S
Overload	A/S
Earth leakage	A/S
Asymmetry between phases	A/S
Maintenance	A/S
High / Low generator frequency	A/S
Engine overspeed	A/S
Engine underspeed	A/S
Generator overvoltage	A/S
Generator undervoltage	A/S
ECU Alert (if applicable)	A/S
Low oil pressure	A/S
Low level of radiator water [f]	A/S
Engine high temperature	A/S
Fuel leakage/ theft	A



6. CONTROL PANEL

ENGINE	Grupel G545
Engine speed	●
Low oil pressure protection	●
Oil pressure reading [c]	○
High temperature engine protection	●
Engine temperature reading [c]	○
Engine battery voltage	●
Intensity of the engine battery [d]	○
Fuel Consumption [e]	●
Low level of radiator water [f]	○
Scheduled engine maintenance	●

COMMUNICATION	Grupel G545
USB female type B (max. 6m)	●
USB female type A [g]	○
RS232 port (max. 15m)	-
RS485 port (max. 1,2Km)	●
Ethernet port RJ45 [g]	○
GSM + location via MLAT [h]	○
ModBus RTU protocol	●
ModBus TCP protocol [g]	○
SNMP protocol [g]	○
CAN port (max. 40m)	●
MSC port (max. 240m) [i]	○
PLC functionality	●

Legenda

● Available

○ Optional

- Not available

A Warning Alarm

S Stop alarm

[a] Need additional CT

[b] No. of outputs available for standard configuration. The outputs do not include relays and additional terminal connections.

[c] If the information is not provided by the engine-ECU, you need an additional sensor

[d] Needs additional ammeter

[e] If information provided by the engine ECU

[f] Required additional sensor

[g] Requires G-ETH

[h] Requires G-GSM

[i] Requires G-Sync

APPLICATIONS	Grupel G545
Automatic or manual start-up	●
Remote start by dry contact	●
Automatic by mains failure	●
Alternating with timesharing	●
Multi-generators synchronization and load sharing (max. 48 generators) [i]	○
Generator-Mains in synchronism and load sharing (1 generator and 1 mains) [i]	○

OPTIONAL EXPANSIONS	Grupel G545
G-08 (8 dig. inputs)	○
G-06 (8 relay outputs)	○
G-GSM (GSM and/or GPS by MLAT)	○
G-ETH (ethernet module)	○
G-ETH (ethernet module according to SNMP protocol)	○
G545 (mirror controller, maximum distance 1km)	○
G175 (convert QTC into QTA)	○
G545 (convert QTC into QTA)	○

STANDARDS

Working temperature	-30 ≤ °C ≤ 70
Protection index (when assembled with sealing gasket)	IP65 - Quando montado com junta de vedação
Degree of humidity (during 48hr)	93%, 40°C durante 48h

Dimensions and weights guidelines. Environmental reference conditions: 100kPa, 25 °C, 30% relative humidity and fuel temperature below 40 °C. Power ratings according to ISO 8528-1:2018.

Emergency power (ESP): Maximum power available to supply variable loads for a maximum period of 200h/year. The average load factor in 24h of operation must not exceed 70% of the ESP regime. It does not allow overload.

Prime power (PRP): Maximum power available to supply variable loads for an unlimited number of hours. The average load factor in 24 hours of operation must not exceed 70% of the PRP rating. Allows an overload of 10% for a maximum period of 1 hour every 12 hours of operation. Overloading may not exceed 25 hours/year.

Continuous power (COP): Maximum power available to supply constant loads for an unlimited number of hours per year, between the maintenance intervals and environmental conditions advertised by the manufacturer.

These specifications are subject to change without notice.

DISTRIBUTOR